




# SMART WiFi GU10 BIORHYTHM GLOBES

## Biorhythm to simulate natural daylight



WiFi  
NO HUB REQUIRED

works with the  
Google Assistant

WORKS WITH  
alexa

Works with  
IFTTT

DIY

GU10 BASE

5W  
350LM

45°  
BEAM  
SPREAD

BIORHYTHM

DIMMING

TUNEABLE  
CCT

3000K  
WARM  
WHITE

TUNEABLE  
RGB

← 22081 →

← 21960 →

**Make your lamps, spotlights and exterior lighting smart with these GU10 globes. Use Biorhythm to help you focus (or relax) throughout your day. It simulates the natural progression of light through the day to benefit your sleep-wake cycle.**

- Biorhythm gradually increases brightness to promote wakefulness and focus during the day before decreasing it to feel more relaxed and ready to sleep at night
- Control from anywhere via app or voice control.
- Create schedules & timing to automate your home.
- Tune the colour temperature from a warm 2700K to a bright daylight 6000K (CCT model)
- Design different colour scenes and brightness so you can easily change its colour or luminosity to suit your mood. (RGB+W model)
- Provides a 45 degree beam with up to 400 lumens of clear, crisp light from a 5W LED light source.
- Fits in most GU10 fittings to make your existing lighting smart.
- Dimmable via app and/or voice control through Amazon Alexa®, Google Assistant®.
- Compatible with BrilliantSmart devices via automation & IFTTT.

### APPLICATIONS

- Biorhythm lighting feature simulates daylight from sunrise to sunset.
- Control lights individually and in groups.
- Using “vacation routines” to turn lights on and off at random intervals to make it seem like you’re home when you’re away






# SMART WiFi GU10 BIORHYTHM GLOBES

## TECHNICAL SPECIFICATIONS

<b>Operating voltage:</b>	220-240V / 50Hz
<b>Wattage:</b>	5W Total
<b>Lumens:</b>	400 Total Lumens
<b>Light adjustable:</b>	Biorythm to simulate daylight from sunrise to sunset 22081: Tune colour temperature within 2700K and 6000K 21960: Millions of colours and 3000K warm white
<b>Beam angle:</b>	45 degrees
<b>Colour rendering index:</b>	> 80
<b>Dimmable:</b>	Yes, via app
<b>Construction:</b>	Polycarbonate, frosted acrylic
<b>Operating temperature:</b>	+5°C to 40°C
<b>WiFi Info:</b>	IEEE802.11b/g/n, 2.4GHz Mac Encryption; WEP/WAPI/TKIP/AES
<b>Device Requirements:</b>	iOS 8.0 or higher, Android 4.1 or higher
<b>Standards:</b>	AS/NZS 62560:2011+A1:2015

## INSTALLATION

Do-it-Yourself installation



	MODEL	BASE	DESCRIPTION	BOX SIZE	GROSS WEIGHT	BOX QTY	BARCODE/TUN
<b>RETAIL BOX</b>	22081	GU10		W65 x H125 x D60 mm	0.05 kg	1 pc	 9 312641 220817 >
<b>INNER CTN</b>	22081	GU10	Smart Wifi GU10 CCT LED Biorythm Globe		0.34 kg	6 pc	 19312641220814
<b>OUTER CTN</b>	22081	GU10			3.95 kg	60 pc	 29312641220811
<b>RETAIL BOX</b>	21960	GU10		W65 x H125 x D60 mm	0.05 kg	1 pc	 9 312641 219606 >
<b>INNER CTN</b>	21960	GU10	Smart Wifi GU10 RGB+W LED Biorythm Globe		0.34 kg	6 pc	 19312641219603
<b>OUTER CTN</b>	21960	GU10			3.95 kg	60 pc	 29312641219600